

EBB69





Refrigeration System

- · Side mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.
- · Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- · Full-length air duct ensures optimal cold air circulation.
- · Time-initiated and temperature-terminated auto defrost cycle for seamless operation.
- · Large capacity, corrosion-resistant condenser and evaporator coils.
- · Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.
- · High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning.
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

Cabinet Construction

Heavy duty stainless steel countertop with textured laminate, black vinyl exterior.

- · Galvanized steel interior walls and high quality stainless steel floor.
- · 13/4" thick high density polyurethane insulation.
- · Built-in caster thread receptacles.

Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

- · Textured laminate, black vinyl exterior with galvanized steel interior.
- ·13/4" thick high density polyurethane insulation.
- · Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, recessed door handles.
- · Pre-installed door locks keep your items safe from theft.

Shelving

- · Two epoxy coated, steel wire shelves per section.
- · Height adjustable stainless steel clips.

Temperature Control

- · Multi-function digital controller with easy to read LED display.
- · Factory preset temperature, 35°F. Temperature setting range from 33°F to 54°F.
- · Audible overheat protection alarm for compressor and condenser coil.

Options

- · Additional shelving.
- · 3" or 5" swivel casters with locks.
- · 3.5" 6" height-adjustable and interchangeable legs.





















Туре	Doors	Capacity Cu. Ft.	12 oz. Cans	12 oz. Bottles	Shelves	Refrigerant	НР	Power V-Hz-Ph	Amps	Crated Weight	Exterior Dimensions		
											L	D	Н*
REF	2	24	800	504	4	R-290	1/4+	115-60-1	3.5	323 lbs	68"	27"	37.25"

BACK BAR COOLER



EBB69

EBB Series

DIMENSIONAL DATA


	L	68 in.		
External Dims.	D	27 in.		
	H*	37.25 in.		
Crated Weight	323 lbs.			
Doors/Drawers/	2			
Max Weight Sup	-			


STORAGE DATA

Net Capacity Cu. Ft. 🟲	24
Shelves	4
Barrels	-
20 oz. Bottles	-
12 oz. Bottles	504
12 oz. Cans	800
8" Mugs	-
# of Pans (Top)	-
# of Pans (Drawer)	-
Dividers	-
Trays	-


ELECTRICAL DATA


Voltage	115-60-1
Full Load Amperage	3.5A
Feed Wires w/ Ground	3
Cord Length	9ft
NEMA Plug Type	(i) NEMA 5-15P





FRONT





SIDE

AIRFLOW

REFRIGERATION DATA

Side
R-290
1/4+
1926

KEY

1721								
L H FD SD	Door Lid Half Door Full Door Solid Door Glass Door	R REF F FRZ DUAL DR	Freezer Freezer REF/FRZ	Refrigerator Refrigerator Freezer Freezer REF/FRZ Combo Drawer				
	Elevation	Right	Plan	3D	Back			

ACCESSORIES & OPTIONS

- Additional Shelving
- AJL03-00
- CASA3-01
- CASA5-01
- Contact Everest Refrigeration for more information.
- Interchangeable Leg for Caster (Optional)

PLAN VIEW

- 3" Overall Height Caster Assembly (2) Front (2) Rear
- 5" Overall Height Caster Assembly (2) Front (2) Rear