



PTAC Made Simple



Traditional experience, premium comfort

With **Distinctions** PTAC units, you have a reliable and high-quality option—while your guests enjoy ideal comfort.



Model		DCP 073A25AA	DCP 073A35AA	DCP 093A25AA	DCP 093A35AA	DCP 123A25AA	DCP 093A35AA	DCP 123A50AA	DCP 153A50AA	DCP 153A35AA
Cooling										
Voltage		208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230
Capacity (BTU/h)		7,200 / 7,000	7,200 / 7,000	9,200 / 9,000	9,200 / 9,000	12,000 / 11,800	12,000 / 11,800	12,000 / 11,800	14,700 / 14,500	14,700 / 14,500
Amps		2.45 / 2.60	2.45 / 2.60	3.54 / 3.83	3.54 / 3.83	4.9 / 5.3	4.9 / 5.3	4.9 / 5.3	6.03 / 6.58	6.03 / 6.58
Watts		550 / 535	550 / 535	814 / 796	814 / 796	1,121 / 1,102	1,121 / 1,102	1,121 / 1,102	1,390 / 1,370	1,390 / 1,370
EER		13.1	13.1	11.3	11.3	10.7	10.7	10.7	10.6	10.6
CFM (cool/ wet coil)	high	334	334	435	435	384	384	384	376	376
	low	236	236	341	341	311	311	311	315	315
CFM (dry)	high	334	334	435	435	384	384	384	376	376
	low	237	237	341	341	311	311	311	315	315
Universal										
Vent door CFM		61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56
Dehumidification (pints/hr.)		0.63	0.63	1.18	1.18	2.75	2.75	2.75	4.55	4.55
Net weight (lbs.)		101.63	101.63	98.1	98.1	108.69	108.69	108.69	113.1	113.1
Ship weight (lbs.)		112.43	112.43	108.69	108.69	119.49	119.49	119.49	122.8	122.8
CFM (dry)		334	334	435	435	384	384	384	376	376
Electric Heat										
Voltage		208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230
Heater size (kW)		2.5	3.5	2.5	3.5	2.5	3.5	5	5	3.5
Heating capacity (BTU/h)		7,800 / 6,300	10,900 / 8,900	7,800 / 6,300	10,900 / 8,900	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	15,000 / 12,200	10,900 / 8,900
Watts		2,535 / 2,080	3,519 / 2,850	2,535 / 2,080	3,535.5 / 2,897	2,535 / 2,080	3,535 / 2,900	4,769 / 3,953	4,769 / 3,953	3,535 / 2,900
Amps		10.8 / 9.8	15.30 / 13.70	10.8 / 9.8	15.3 / 13.7	10.8 / 9.8	15.3 / 13.7	22 / 19.7	22 / 19.7	15.3 / 13.7



Model		DHP 093A25AA	DHP 093A35AA	DHP 123A25AA	DHP 123A35AA	DHP 123A50AA	DHP 153A35AA	DHP 153A50AA	DHP 094A35AA	DHP 124A35AA
Cooling										
Voltage		208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265
Capacity (BTU/h)		9,000 / 8,800	9,000 / 8,800	12,000 / 11,800	12,000 / 11,800	12,000 / 11,800	14,700 / 14,500	14,700 / 14,500	9,000	12,000
Amps		3.46 / 3.75	3.46 / 3.75	5.0 / 5.4	5.0 / 5.4	5.0 / 5.4	6.03 / 6.58	6.03 / 6.58	3.01	4.31
Watts		796 / 778	796 / 778	1,142 / 1,124	1,142 / 1,124	1,142 / 1,124	1,390 / 1,370	1,390 / 1,370	796	1,142
EER		11.4	11.4	10.5	10.5	10.5	10.6	10.6	11.3	10.5
CFM (cool/ wet coil)	high	431	431	387	387	387	374	374	388	379
	low	333	333	309	309	309	312	312	321	313
CFM (dry)	high	431	431	387	387	387	374	374	388	380
	low	333	333	309	309	309	312	312	322	314
Universal										
Vent door CFM		61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	61.1 / 57.6 / 50.6	62 / 60 / 56
Dehumidification (pints/hr.)		1.06	1.06	2.81	2.81	2.81	4.29	4.29	1.06	2.81
Net weight (lbs.)		102.51	102.51	115.96	115.96	115.96	116.84	116.84	101.19	113.1
Ship weight (lbs.)		112.88	112.88	125.44	125.44	125.44	126.54	126.54	111.99	126.76
CFM (dry)		431	431	387	387	387	374	374	388	380
Electric Heat										
Voltage		208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265
Heater size (kW)		2.5	3.5	2.5	3.5	5	3.5	5	3.5	3.5
Heating capacity (BTU/h)		7,800 / 6,300	10,900 / 8,900	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	10,900 / 8,900	15,000 / 12,200	10,900	10,900
Watts		2,535 / 2,080	3,535.5 / 2,897	2,535 / 2,080	3,535 / 2,900	4,769 / 3,953	3,535 / 2,900	4,769 / 3,953	3,500	3,500
Amps		10.8 / 9.8	15.3 / 13.7	10.8 / 9.8	15.3 / 13.7	22 / 19.7	15.3 / 13.7	22 / 19.7	13.46	13.46
Reverse Cycle										
Voltage		208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265
Capacity (BTU/h)		8,100 / 7,900	8,100 / 7,900	10,800 / 10,500	10,800 / 10,500	10,800 / 10,500	13,500 / 13,200	13,500 / 13,200	8,100	10,800
Amps		3.04 / 3.28	3.04 / 3.28	4.3 / 4.6	4.3 / 4.6	4.3 / 4.6	5.38 / 5.82	5.38 / 5.82	3.1	4.3
Watts		700 / 680	700 / 680	990 / 963	990 / 963	990 / 963	1,237 / 1,209	1,237 / 1,209	719	989
COP		3.40	3.40	3.2	3.2	3.2	3.20	3.20	3.3	3.2



Sales, Support and Service You Can Trust

Five-Year Limited Warranty: Enjoy one of the most comprehensive warranties in the industry: First Year: parts & labor; Second through fifth years: parts & labor on certain sealed system components; second through fifth years: on certain functional parts only. For complete warranty details, visit www.distinctions-ptac.com.

Distinctions PTAC are stocked and sold from the same warehouse as the **Amana® Brand PTAC** products you have come to love over the years.

Features

Dual Fan Motors: Allows precise independent fan speed operation while providing quiet operation.

LCDI Power Cord Included: No need to match power cord type to unit size.

3-Speed Fan: Provide precise comfort control to your guests.

Constant Fan: Take advantage of each unit's dual options—select continuous fan operation or cycle the fan ON and OFF with the thermostat. Our 7-button design allows guests to select fan.

Wired Thermostat Compatible: Wire your PTAC with any standard thermostat for better temperature control

Advantages

Energy Efficiencies: With EERs up to 13.1 and COPs up to 3.4, our unit's high efficiencies may qualify you for many of the rebates offered by electrical power companies.

Automatic Emergency Heat: No more "my unit is not heating" complaints during the middle of the night. Heat pump units will automatically switch over to electric resistance heat if the heat pump compressor system fails or if the heating load is greater than the unit capacity.

Easy Pull-Out Filters: Our filters are washable and easy to maintain.

Condensate Dispersion System: Our condensate dispersion system removes condensate from indoor cooling operation by throwing water directly on to the outdoor coil for rapid evaporation and increased cooling efficiencies.

PTAC Direct Sales, Inc.
185 S. Kimball Ave.
Suite 130
Southlake, TX 76092
877.454.7822 (T)
877.647.6408 (F)



Amana® is a registered trademark of Maytag Corporation or its related companies and is used under license. All rights reserved.

Our continuing commitment to quality products may mean a change in specifications without notice.
©2022 Daikin Comfort Technologies Manufacturing L.P. • Houston, Texas • Printed in the USA.