

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

SHALLOW DEPTH WORKTOP REFRIGERATOR

WTR34HC Solid Door With Foamed-In Place Backsplash Hydrocarbon Series

MODEL: WTR34HC-FIP



*Note: Shown with optional full electronic control

5 Year Parts/Labor Warranty Available 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel front, sides, door and grille (galvanized back & bottom)
- Interior liner is made of corrosion resistant aluminum
- Stainless steel top for added durability Foamed-in place backsplash
- Foamed-in place backsplash
- Mechanical control
- Interior thermometer is standard
- Self-closing doors with 120° stay-open feature, on lift-off style hinges
- Easy door removal for service and cleaning
- Magnetic gasket attached to each door for positive seal
- . 6" Casters, two (2) with brakes standard
- Four (4) epoxy-coated steel wire shelves
- Field-reversible doors (hinge kit not included)

OPTIONS & ACCESSORIES

- 3 Year parts/labor standard, additional 2 year warranty available
- Stainless steel back
- Stainless steel interior
- 16 Gauge stainless steel top
- Full electronic control*
- Additional shelves
- Shelf clips
- · Glass door option
- · Right or left hinged door
- Locks (solid doors only)
- · Wire shelf divider
- · Cutting board
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- · Low profile casters
- Roller kit
- Remote option** (see note on back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerators capable of maintaining product temperature between 36°F and 38°F












MODEL	WTR34HC-FIP	
EXTERNAL DIMENSIONAL DATA		
Width Overall	34"	
Depth Overall with Handle & Bumper	24 ½"	
Height Overall with 6" Casters	36 ⅓"	
Number of Doors	2	
Depth with Door Open 90°	38"	
Door Openings	13 ½" x 18"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	5.96	
Internal Width Overall	30"	
Internal Depth Overall	13"	
Internal Height Overall	19 ½"	
Number of Shelves	4	
ELECTRICAL DATA		
Full Load Amperes	2.0	
REFRIGERATION DATA		
Horsepower	1/6	
Capacity (BTU/Hr)	1110	
Heat Rejection (BTU/Hr)	1665	
Charge (lbs/grams/ounces)	0.1323 / 60 / 2.12	
SHIPPING DATA		
Gross Weight - Crated	174 lbs	
Height - Crated	43"	
Width - Crated	30"	
Depth - Crated	32"	

^{**}NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

Worktop Refrigerator - Shallow Depth Model: WTR34HC-FIP





ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.